



Description

WBEQ™ is a clear two component water based epoxy coating designed with quick curing aspects of solvent based products but, with extremely low odors. WBEQ™ is not designed for topcoat over colored floors.

Recommended Uses

WBEQ™ is recommended for jobs that require a quick curing primer with low odors on concrete, wood and metal. WBEQ™ has excellent chemical and abrasion resistance.

Advantages

- Penetrating primer.
- Tack free within 2hrs
- Can be applied in single coat.
- Very low VOC's.
- Excellent abrasion resistance.
- Strong chemical resistance.

Available in the following quantities

- 2 gallon kit
- 5 gallon kit

Characteristics	Liquid
Color	Clear (not water clear)
VOC	1.2 lbs per gal
Solid Content	42%
Ratio	4:1
Coverage	225-300 sqft per/gal
Cure schedule	@70°
Application Temp	50°-90° Humidity >85%
Pot Life	2 hrs
Tack free	1.5 -3 hrs
Recoat / Topcoat	2-5 hrs
Light Foot Traffic	6-10 hrs
Full cure	2-5 days
Mil Thickness	5-7 mils
Adhesion	430psi @elcometer (concrete failure, no delamination)
Abrasion Resistance	Taber adrasor CS-17 calibrase wheel with 1000 gram total load and 500 cycles = 45 mg loss
Gloss	>60@60 degrees
Viscosity	Mixed=400-900 cps
Flexural Strength	8200 psi@ ASTMD638

Disclaimer: The info herein is general to assist our customers in determining whether TruCrete Inc. products are suitable for their specific applications. TruCrete Inc. products are intended for sale to trained installers. We recommend that customers inspect and test our products before use to satisfy themselves as to the content and suitability for the applications they intend to use TruCrete Inc. products for. Nothing herein shall constitute any warranty expressed or implied, including any warranty of merchantability or fitness for a particular purpose, nor is any protection from any law or patent to be inferred. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for incidental or consequential damages.