



# COLOR SHADE™

## Universal Color Pigment

### Description

Color Shade™ universal color pigment is a synthetic iron oxide pigment blend packaged in 1 lb. bags for easy application in the field. Many colors are available, see color chart for reference.

### Recommended Uses

Color Shade™ universal color pigment is used as an integral concrete and concrete resurfacing colorant. -May also be used for pigmenting Infused™ concrete stain, for staining & highlighting decorative concrete and overlays. May also be used to tint clear carriers such as sealers, liquid release agents, urethanes and epoxies.

### Advantages

- Extremely concentrated.
- Color fast/will not fade.
- No health hazards.
- Very versatile
- May be used to color just about anything.
- Perfect for interior and exterior applications.
- Zero VOC's - Blends with water & solvent carriers

Appearance	Dry colored powder
VOC	None
PH Value	4-7 in aqueous suspension
Vapor Pressure	N/A
Vapor Density	N/A
Boiling Point	N/A
Melting Point	Greater than 1,832° F
Specific gravity (g/ml)	3.8-4.1 @68° F
Bulk density (kg/m3)	350-600 @68° F
UV Stability	Excellent

Available in the following:

- 1lb. bags for easy onsite application
- More quantities available upon request

Disclaimer: The info herein is general to assist our customers in determining whether TruCrete Surfacing Systems® products are suitable for their specific applications. TruCrete Surfacing Systems® products are intended for sale to trained installers. We recommend that customers inspect and test our products before use to satisfy themselves as to the content and suitability for the applications they intend to use TruCrete Surfacing Systems® products for. Nothing herein shall constitute any warranty expressed or implied, including any warranty of merchantability or fitness for a particular purpose, nor is any protection from any law or patent to be inferred. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for incidental or consequential damages.

TruCrete Inc® All Rights Reserved  
443-205-4547: info@trucrete: www.trucrete.com