



Crack Attack™

Quick Curing Concrete Crack Filler

Description

Crack Attack™ concrete crack filler is a quick curing hybrid polymer resin, with a very rapid set time.

Recommended Uses

Crack Attack™ concrete crack filler is used to fill stable cracks in concrete, to fix spalled concrete areas, and for small patching.

Advantages

- Low viscosity to easily penetrate cracks as small as 1/32", effectively sealing them off from damage and degradation.
- Very fast set time.
- Water based.
- Grind-able in 15 minutes.
- Broad application temperature range.
- Very low odor.
- No mess packaging.
- Thin viscosity for penetration.
- Quick return to service.

Appearance & Physical State	liquid
Mixing Ratio	1:1
Smell	Solvent
Dries	Grey color
VOC	<450g/l
NVM	58%
Application Temperature	50°-85° F
Coverage	462 cubic inches per 2 gallon kit 36 cubic inches per 600ml cartridge
Gel Time	3-6min
Tack Free	10 min
Tensile Strength	4,200 psi
Tensile Elongation	3%
Bond Strength	4,154 psi

Available in many sizes

- 600ml cartridge
- 2 gallon kit
- 10 gallon kit

Disclaimer: The info herein is general to assist our customers in determining whether TruCrete Surfacing Systems® products are suitable for their specific applications. TruCrete Surfacing Systems® products are intended for sale to trained installers. We recommend that customers inspect and test our products before use to satisfy themselves as to the content and suitability for the applications they intend to use TruCrete Surfacing Systems® products for. Nothing herein shall constitute any warranty expressed or implied, including any warranty of merchantability or fitness for a particular purpose, nor is any protection from any law or patent to be inferred. The exclusive remedy for all proven claims is replacement of our materials and in no event shall we be liable for incidental or consequential damages.

TruCrete Inc® All Rights Reserved
443-205-4547: info@trucrete: www.trucrete.com